




Features

- High gloss acrylic surface
- Comfortable one piece 18" tall seat.
- Scratch and stain resistant
- Spacious slip resistant area
- Reinforced with fiberglass and A Pro-Strength Core for maximum support
- Secure to subfloor, screw flange direct to studs
- No predrilling or clips required
- Covered with protective film to maintain finish and protect during installation

Dimensions	Model #	Shipping Weight
48" x 34" x 19" SFR Right - White	LEBSL014834	59 lbs
48" x 34" x 19" SFR Right - Biscuit	LEBSL094834	59 lbs

Color Options*



01
White





09
Biscuit



**Color shown may vary slightly from the actual product due to variations in the printing process of this document. Plumbing accessories not included.*


48" x 34" x 19"
Standard Floor Rough



 = required stud location

 = suggested stud location

Reinforced 7-Layer Construction for Zero-Flex Durability.



The Manufacturer
certifies conformance
to the following
requirements:
CSA B45.5-17
IAPMO Z124-2017

Lyons

Contact Us

Lyons Industries, Inc.

 30000 M-62 West Dowagiac, MI 49047

 (800) 458-9036

 LyonsSupport@lyonsindustries.com

 www.lyonsindustries.com

Design and features may change without notice.

Complies with ANSI Z124.1 and CAN/CSA-B45

CAN/ULC S102.2 Flame-75 & Smoke Developed-485 code.

Complies with ASME:A1.9.7 and CAN/CSA-B45.10

All product subject to manufacturing tolerance of [+] or [-] 1/8".

Printed in U.S.A.