



Features

- Spacious bathing area with molded lumbar support for bathing comfort
- Easy installation for both new construction and remodel projects
- Secure to subfloor, screw flange direct to studs
- No predrilling or clips required
- Covered with protective film to protect finish during installation
- Reinforced integral apron with supports

Dimensions	Model #	Shipping Weight
60" x 32" x 19" SFR Right - White	LLT01603219R	78 lbs
60" x 32" x 19" SFR Right - Biscuit	LLT09603219R	78 lbs
60" x 32" x 19" SFR Left - White	LLT01603219L	78 lbs
60" x 32" x 19" SFR Left - Biscuit	LLT09603219L	78 lbs

Color Options*



01
White





09
Biscuit



**Color shown may vary slightly from the actual product due to variations in the printing process of this document. Plumbing accessories not included.*

60" x 32" x 19"
68 Gallons
Standard Floor Rough




⊠ = required stud location

⊠ = suggested stud location

RH installation shown - reverse for LH installation.

Reinforced 7-Layer Construction
for Zero-Flex Durability.



Contact Us

Lyons Industries, Inc.

30000 M-62 West Dowagiac, MI 49047

(800) 458-9036

LyonsSupport@lyonsindustries.com

www.lyonsindustries.com

Design and features may change without notice.

Complies with ANSI Z124.1 and CAN/CSA-B45

CAN/ULC S102.2 Flame-75 & Smoke Developed-485 code.

Complies with ASME:A1.19.7 and CAN/CSA-B45.10

All product subject to manufacturing tolerance of $\pm$ or $\mp$ 1/8".

Printed in U.S.A.